



DCN-FV Flush Voting Panel



- ▶ **Stylish and modern design (IF award)**
- ▶ **External 'Present' contact**
- ▶ **LED vote confirmation indicators**
- ▶ **LED unit active indicator**

The Flush Voting Panel allows attendance registration and six types of voting: parliamentary, audience response, multiple choice, opinion poll, rating and for/against.

The Flush Voting Panel has an external present contact, which can be used for an external present or fraud switch. Fingerprint readers are typical for the external present contact use.

The Flush Voting Panel can be click-to-fit mounted in a metal panel with a thickness of 2 mm, or can be mounted in combination with DCN-FCOUP coupling pieces and DCN-FEC end caps in any surface. The Flush Voting Panel is connected to the Dual Delegate Interface (DCN-DDI).

Functions

Controls and Indicators

Front

- Five voting buttons with yellow confirmation indicators to prompt the user to indicate presence, to vote and to confirm registration of what is voted. The buttons and indicators work as follows:
 - Yes (+), no (-) and abstain (x) (used for attendance registration, parliamentary voting and for/against)
 - Numerals 1 to 5 (used for multiple choice, opinion polls and rating)
 - Rating scale: --, -, 0, +, ++ (used for audience response)

- One blue LED unit active indicator to show that the system is in normal operation

Interconnections

- Two RJ11 connectors: one for connection to DCN-DDI Dual Delegate Interface, and one for loop through
- Connector for an external present contact (AMP173977-3 socket)

Technical Specifications

Mechanical

Mounting	Click-to-fit in a metal panel with a thickness of 2 mm, or in combination with DCN-FCOUP couplings and DCN-FEC end caps in any surrounding
Dimensions (H x W x D)	40 x 100 x 82 mm (1.57 x 3.94 x 3.23 in)
Weight	81 g (0.18 lb)
Color	
DCN-FV	Silver (RAL 9022)

Ordering Information

DCN-FV Flush Voting Panel
flush mounted, silver

DCN-FV

Americas:

Bosch Communications Systems
12000 Portland Avenue South
Burnsville, Minnesota, 55337, USA
Phone: +1-800-392-3497
Fax: +1-800-955-6831
audiosupport@us.bosch.com
www.boschcommunications.us

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: +31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Bosch Security Systems Pte Ltd
38C Jalan Pemimpin
Singapore 577180
Phone: +65 6319 3450
Fax: +65 6319 3499
apr.securitysystems@bosch.com
www.boschsecurity.com

Represented by