

WGE Weatherproof Low-profile Strobes and Horn Strobes

www.boschsecurity.com



BOSCH
Invented for life



- ▶ Wide voltage range, 16 to 33 VDC or FWR
- ▶ 75 cd strobe meets ADA 4.28.3 requirements
- ▶ Listed for outdoor use when used with the GOELP outdoor enclosure
- ▶ Jumper selection for high or low frequency and for temporal Code 3 or continuous tone patterns
- ▶ Separate horn and strobe functions; silences horn while strobes remain flashing

The Gentex WGE family of weatherproof low-profile strobes and horn strobes offer dependable visible and audible alarms. The horns have a synchronizable (using the AVSM Synchronization Module) chime and whoop tones. You can select high or low volume and choose a 2400 Hz (remote signaling) tone or a low frequency (1500 Hz to 3000 Hz) mechanical sounding tone where doors could prevent hearing the other tone. They are easily field-changeable from temporal Code 3 to a continuous tone. They are shipped from the factory on the temporal lower frequency mode, and come standard with a rugged die-cast metal mounting plate. The strobes have a low operating current and a minimum flash rate of 1 Hz regardless of the input voltage.

These devices are equipped with the SuperSlide feature to test supervision and the Instant Voltage Verification feature for measuring voltage drop draw. The GOELP Low-profile Outdoor Enclosure that creates a surface-mount look is included with each unit. The unit and GOELP enclosure must be used together to meet the UL outdoor listing.

Certifications and approvals

Gentex Corporation hold these listings and approvals:

Region	Certification
USA	UL ULSZ: Audible-signal Appliances (ANSI/UL 464), ULSZ7: Audible-signal Appliances Certified for Canada (CAN/ULC-S525), UVAV: Visual-signal Appliances for Fire-protective Signaling Systems (ANSI/UL 1638), and UEES7: Visual-signal Appliances Certified for Canada [CAN/ULC-S526 (1987)]
	CSFM see our website

Installation/configuration notes

Compatible Products

The following products are compatible with these strobes:

Control Panels:

Active¹: FPA-1000 family and FPD-7024 family

Legacy¹: D10024A, D9412, D8024, D7024², and D7022³

Synchronization Modules:

AVSM-R and AVSM-W

¹ For synchronization, use the AVSM-R or AVSM-W Synchronization Modules with these control panels.

² When used with a D7039 Multiplex Expansion Module, the D7024 becomes an addressable fire alarm control panel (FACP).

³ The D7022 must be set for 24 VDC operation and requires the AVSM-R or AVSM-W Synchronization Modules for synchronization.

Mounting Considerations

For an outdoor application or a severe environment (NEMA 3R) application, the WGES Strobes in GOELP Outdoor Enclosures are to be mounted on a flat wall on a universal electrical box. The enclosure is supplied; the electrical box is not supplied.

Wiring**Notice**

Do not use these units in coded or pulsed signaling circuits.

The input terminals accept wires with diameters between 18 AWG and 12 AWG (ISO 0.75 mm² and 4 mm²).

Parts included

Quant.	Component
1	Strobe or horn strobe with finish plate
1	Die-cast mounting plate
1	GOELP low-profile outdoor enclosure
1	Plastic test card
1	Hardware pack
1	Literature pack

Technical specifications**Environmental Considerations****Temperature (Operating):**

- | | |
|-----------|----------------------------------|
| • Indoor | +32°F to +120°F (0°C to +49°C) |
| • Outdoor | -31°F to +150°F (-35°C to +66°C) |

Mechanical Properties

Candela Rating	75 cd
----------------	-------

Dimensions (HxWxD):

without GOELP enclosure	5 in. x 4.5 in. x 2.5 in. (12.7 cm x 11.4 cm x 6.4 cm)
with GOELP enclosure	5.75 in. x 4.75 in. x 3.25 in. (14.6 cm x 12.1 cm x 8.3 cm)

Power Requirements

Strobe Current (maximum)	180 mA RMS; 245 mA FWR
--------------------------	------------------------

Voltage (Input):

- | | |
|-----------|--------------------------------|
| • nominal | 24 VDC or FWR |
| • range | 16 VDC or FWR to 33 VDC or FWR |

All hardware and software product names used in this document are likely to be registered trademarks and must be treated accordingly.

Ordering information**WGEC24-75WRLP Weatherproof Low-profile Horn Strobe (red)**

This red low-profile, wall-mount horn strobe offers dependable visible and audible alarms for all outdoor needs.

Order number **WGEC24-75WRLP**

WGEC24-75WWLP Weatherproof Low-profile Horn Strobe (off-white)

This off-white low-profile, wall-mount horn strobe offers dependable visible and audible alarms for all outdoor needs.

Order number **WGEC24-75WWLP**

WGES24-75WRLP Weatherproof Low-profile Strobe (red)

This red low-profile, wall-mount strobe offers dependable visible and audible alarms for all outdoor needs.

Order number **WGES24-75WRLP**

WGES24-75WWLP Weatherproof Low-profile Strobe (off-white)

This off-white low-profile, wall-mount strobe offers dependable visible and audible alarms for all outdoor needs.

Order number **WGES24-75WWLP**

Accessories**AVSM-R Synchronization Control Module (red)**

Synchronization module for use with all Gentex synchronizable notification appliances except the HS24 Series and the ST24 Series.

Not Available.

Order number **AVSM-R**

AVSM-W Synchronization Control Module (white)

Synchronization module for use with all Gentex synchronizable notification appliances except the HS24 Series and the ST24 Series.

Not Available.

Order number **AVSM-W**

Represented by:

Americas:

Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security
Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd.
201 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

America Latina:

Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
latam.boschsecurity@bosch.com
www.boschsecurity.com