

## F01U511350 SmartKey, standard key



An intrusion alarm system is armed and disarmed using an electronic key on the reader. For various functions, the SmartKey key requires an additional push on the key button.

### Regulatory information

Region	Regulatory compliance/quality marks	
Europe	CE	SmartKey

### Parts included

Quantity	Component
1	Standard key without security card

### Technical specifications

#### Environmental

#### Mechanical

Operating temperature (°C)	-40 °C – 70 °C
Storage temperature (°C)	-40 °C – 85 °C
Environmental class (EN 50130-5)	IV

- ▶ Electronic key for arming/disarming of an intrusion interface
- ▶ Support for Smartkey readers
- ▶ For various functions, the key requires an additional push of the key button

IP rating	IP67
Dimensions (H x W x D) (mm)	54 mm x 27 mm x 6 mm
Weight (g)	11 g
Housing material	POM
Color (RAL)	RAL 9005 Jet black
Maximum range (mm)	20 mm
Code options	10 <sup>7</sup>

### Ordering information

**F01U511350 SmartKey, standard key**  
 1 x SmartKey key without security card  
 Order number **F01U511350** | **F.01U.511.350**

#### Represented by:

**Europe, Middle East, Africa:**  
 Bosch Security Systems B.V.  
 P.O. Box 80002  
 5600 JB Eindhoven, The Netherlands  
[www.boschsecurity.com/xc/en/contact/](http://www.boschsecurity.com/xc/en/contact/)  
[www.boschsecurity.com](http://www.boschsecurity.com)

**Germany:**  
 Bosch Sicherheitssysteme GmbH  
 Robert-Bosch-Platz 1  
 D-70839 Gerlingen  
[www.boschsecurity.com](http://www.boschsecurity.com)

**North America:**  
 Bosch Security Systems, LLC  
 130 Perinton Parkway  
 Fairport, New York, 14450, USA  
[www.boschsecurity.com](http://www.boschsecurity.com)

**Asia-Pacific:**  
 Robert Bosch (SEA) Pte Ltd, Security Systems  
 11 Bishan Street 21  
 Singapore 573943  
[www.boschsecurity.com/xc/en/contact/](http://www.boschsecurity.com/xc/en/contact/)  
[www.boschsecurity.com](http://www.boschsecurity.com)