



# MH 400 Detector Heating Element

The Detector Heating Element MH 400 is usable at locations where the functional safety of the detector might be impaired by condensation (dew), e. g. in warehouses which are briefly opened in order to allow vehicles to enter and leave.

## Installation/Configuration Notes

- The integrated 1 k $\Omega$  resistor has a nominal performance of 3 W. With a looped-through 28 V power supply (monitored), up to 10 Detector Heating Elements MH 400 can be deployed per loop.
- External power supply (not monitored) is possible.
- The supply voltage may not be permitted to fall below 23 V.

## Ordering Information

<b>MH 400 Detector Heating Element</b>	<b>MH 400</b>
usable at locations where the functional safety of the detector might be impaired by condensation	

**Americas:**  
Bosch Security Systems, Inc.  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
security.sales@us.bosch.com  
www.boschsecurity.us

**Europe, Middle East, Africa:**  
Bosch Security Systems B.V.  
P.O. Box 80002  
5600 JB Eindhoven, The Netherlands  
Phone: + 31 40 2577 284  
Fax: +31 40 2577 330  
emea.securitysystems@bosch.com  
www.boschsecurity.com

**Asia-Pacific:**  
Robert Bosch (SEA) Pte Ltd, Security Systems  
11 Bishan Street 21  
Singapore 573943  
Phone: +65 6258 5511  
Fax: +65 6571 2698  
apr.securitysystems@bosch.com  
www.boschsecurity.com

**Represented by**