

NPD-6001C Midspan, bt, 60W, indoor

PoE Midspan



The PoE Midspan enables remote PoE power for compatible IP PTZ cameras from Bosch. The PoE Midspan generates a maximum of 60 W and complies to the IEEE 802.3bt standard. The PoE Midspan has a single port and provides power on all 4 pairs.

Regulatory information

Standard	Type	
Regulatory compliance	IEEE 802.3bt (PoE)	
	RoHS compliant	
	WEEE compliant	
	CE	
Electromagnetic emission & immunity	FCC Part 15, Class B	
	EN 55032 Class B (emissions)	
	EN 55024 (immunity)	
	VCCI	
Safety	UL/IEC/EN 60950-1 (ed. 2)	
Region	Regulatory compliance/quality marks	
Europe	CE	


Installation/configuration notes

Notice
Use only with cameras that support the IEEE 802.3bt standard.



- Makes PoE cameras easy to install
- Plug-and-play installation
- Safe: low power devices receive only the power they need
- Automatic detection and protection of non-standard Ethernet terminals
- Compact design fits easily in WLAN access point and IP camera installations

See the datasheet for your camera, make sure the midspan you will use is listed as the accessory.



- | | |
|---------------|-------------|
| 1 Switch | 2 Data |
| 3 PoE midspan | 4 IP camera |
| 5 Power | 6 UPS |

Parts included

Quantity	Component
1	PoE Midspan

Quantity	Component
1	Power cord, 110 VAC
1	Power cord, 230 VAC
1	Quick installation guide

Technical specifications

Electrical

PoE input	IEEE 802.3bt type 3 compliant
PoE output pin assignment and polarity	Data pairs 1/2 (-) and 3/6 (+); spare pairs 7/8 (-) and 4/5 (+); spare pairs 7/8 (-) and 4/5 (+)
PoE output power voltage (VDC)	55 VDC
PoE output user port power (W)	60 W over 4-pairs (guaranteed)
Input voltage (VAC)	100 VAC – 240 VAC (± 10%)
Input current (A)	1.50 A at 100 - 240 VAC
AC frequency (Hz)	50 - 60 Hz
Maximum heat loss (BTU/h)	34.20 BTU/h at 100 VAC

Connectivity

Number of ports	1
Data rates (Mbps)	10/100/1000 Mbps
Connectors	Shielded RJ-45, EIA 568A, 568B
Reliability	MTBF: 240,000 h at 25 °C

Operation

AC power indicator	Yellow
Channel power indicator	2 pairs - blue on; 4 pairs - green on

Environmental

Operating temperature (°C)	0 °C – 40 °C
Operating temperature (°F)	32 °F – 104 °F
Storage temperature (°C)	-20 °C – 70 °C

Storage temperature (°F)	-4 °F – 158 °F
Operating relative humidity, non-condensing (%)	95%
Storage relative humidity (%)	95%
Usage	Indoor

Construction

Dimensions (H x W x D) (mm)	38 mm x 62 mm x 151 mm
Dimensions (H x W x D) (in)	1.50 in x 2.44 in x 5.94 in
Weight (g)	340 g
Weight (lb)	0.74 lb
Color	White
Mounting type	Surface-mounted; Wall-mounted

Ordering information

NPD-6001C Midspan, bt, 60W, indoor

Indoor midspan with Power-over-Ethernet for use with PoE-enabled cameras; 60 W, single-port, AC input
Order number **NPD-6001C**



<https://www.boschsecurity.com>