

PRA-SFPSX Fiber transceiver, multimode

PRAESENSA



- ▶ Industry standard small form-factor pluggable (SFP)
- ▶ Immovable lock design
- ▶ Hot pluggable
- ▶ Duplex LC connector
- ▶ Full duplex speed support


The PRA-SFPSX is a compact fiber transceiver for multi-mode fibers, covering distances up to 550 m. This fiber transceiver is an OEM transceiver, made for Bosch by Advantech for use in Bosch Public Address and Voice Alarm systems. It locks into the SFP socket of the PRAESENSA multifunction power supply and Ethernet switch. It is compliant with Fast Ethernet and IEEE 802.3z Gigabit Ethernet standards for maximum performance, reliability and flexibility. The PRA-SFPSX is certified for EN 54-16 in combination with PRAESENSA systems.


Functions

Features


- Features a duplex LC connector; one connection for transmit and the other for receive.
- Fits and locks into the SFP socket of the PRA-MPSx and PRA-ES8P2S.
- SFP is the popular industry format jointly developed and supported by many network component vendors, providing a connection to different types of optical fiber.
- The PRA-SFPSX supports multi-mode fiber for distances up to 550 m.
- Wide temperature range for maximum reliability.
- Certified for EN 54-16 in combination with PRAESENSA systems.

Connection and functional diagram



LC	Dual lockable transmitter and receiver connector	T	Transmitter
R	Receiver		Controller

Physical connections



Architects' and engineers' specifications

The SX fiber transceiver shall be a wide temperature Small Form-factor Pluggable (SFP) for use with multi-mode fiber and IR light with a wavelength of 850 nm, to cover glass fiber link lengths of up to 550 m. It shall be certified for EN 54-16 in combination with Bosch PRAESENSA systems for public address and voice alarm purposes. The transceiver shall be marked for UL and CE and be compliant with the RoHS directive. Warranty shall be three years minimum. The SX-transceiver shall be a Bosch PRA-SFPSX.

Regulatory information

Emergency standard certifications

Europe	EN 54-16 (0560-CPR-182190000)
International	ISO 7240-16
Maritime applications	DNV GL Type Approval

Emergency standard compliance

Europe	EN 50849
UK	BS 5839-8

Regulatory areas

Safety	Laser Class I IEC 60825-1
Immunity	EN 55035
Emissions	EN 55032 EN 61000-3-2 EN 61000-3-3
Environment	EN/IEC 63000

Parts included

Quantity	Component
1	SFP fiber transceiver

Technical specifications

Quick overview

Operating voltage (VDC)	3.30 VDC
Power consumption (W)	0.50 W maximum
Transmitter power	-9.5 dBm minimum
Receiver sensitivity	-18 dBm maximum
Connector type	Dual LC

Wavelength (nm)	850 nm
Optical fiber	Multi-mode
Core size	50 µm; 62.5 µm
Cable length (m) (50 µm)	550 m maximum
Cable length (m) (62,5 µm)	220 m maximum
Additional features	Hot pluggable; Locking
Ethernet type	1000BASE-SX
Compatibility	MSA standard
Wi-Fi standard	IEEE 802.3z
Operating temperature (°C)	-20 °C – 85 °C
Operating relative humidity, non-condensing (%)	5% – 95%
Storage temperature (°C)	-40 °C – 85 °C
Dimensions (H x W x D) (mm)	13.40 mm x 8.50 mm x 56.50 mm
Weight (g)	75 g

Electrical

Interface	
Supply voltage	3.3 V
Power consumption	0.5 W
Speed	IEEE 802.3z 1000BASE-SX
Transmitter power	-4 – -9.5 dBm
Receiver sensitivity	< -18 dBm
Connection	Hot swappable, Locking

Optical

Interface	
Connector type	Dual LC
Wave length	850 nm
Fiber length	
50 µm core	< 550 m (1.804 ft)
62.5 µm core	< 220 m (722 ft)
Optical fiber	Multi-mode

Interface

Core size	50 µm / 62.5 µm
-----------	-----------------

Environmental**Climatic conditions**

Temperature	
Operating	-20–85 °C (-4–185 °F)
Storage and transport	-40–85 °C (-40–185 °F)
Humidity (non condensing)	5–95%

Mechanical**Enclosure**

Dimensions (HxWxD)	13.4 x 8.5 x 56.5 mm (0.53 x 0.33 x 2.2 in)
Weight	75 g (0.17 lbs)

Ordering information**PRA-SFPSX Fiber transceiver, multimode**

1000BASE-SX SFP module for multi-mode fiber (550 m)

Order number **PRA-SFPSX | F.01U.352.104****Represented by:**

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: + 31 40 2577 284
www.boschsecurity.com/xc/en/contact/
www.boschsecurity.com

Germany:
Bosch Sicherheitssysteme GmbH
Robert-Bosch-Ring 5
85630 Grasbrunn
Tel.: +49 (0)89 6290 0
Fax: +49 (0)89 6290 1020
de.securitysystems@bosch.com
www.boschsecurity.com

North America:
Bosch Security Systems, LLC
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
onlinehelp@us.bosch.com
www.boschsecurity.com

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
www.boschsecurity.com/xc/en/contact/
www.boschsecurity.com